


(ボーリングシステム)ファーストカット
ACCESSORIES for (BORING SYSTEM) FIRSTCUT



スローアウェイ式ジグボーラバイト

FIG.2



最小加工径 D MIN. RANGE	MODEL	CODE	L	L1	L2	φd	チップ INSERT		
8	JBM-1008	700160	50		30	10	CC□□03S1□□		
10	-1010	700161	60	20	40		TP□□0802□□		
12	-1012	700162	70		50				
15	-1015	700163							
18	-1018	700164	79	19	60	16		TP□□1102□□	
8	JBM-1608	700165	65		35		CC□□0602□□		
10	-1610	700166	75	30	45			TP□□0802□□	
12	-1612	700167	85		55				
15	-1615	700168	95			65			
18	-1618	700169					96		26
21	-1621	700170							

Note : 1. Inserts are sold separately.

2. The total length of the square bite is made longer according to the maximum diameter. When using with a small diameter head, cut it before use.

NOTE : Inserts are sold separately.



Technical drawing of a shaft-hub assembly. The drawing shows a shaft of diameter d inserted into a hub of inner diameter D . The length of the shaft is labeled L . The hub has a flange on the right side.

MODEL	CODE	ϕd	ϕD	L
SCP10-6	35650	6	10	17.5
SCP10-8	35652	8		
SCP16-8	35654	8		
SCP16-10	35656	10	16	25
SCP16-12	35658	12		





FIG.2

[illegible]

Note : 1. Inserts are available in 10 pcs boxes.